

1. Unique identification code of the product-type:

## DCP Flexseal NS196 Neutral Silicone

2. **Type, batch or serial number** or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging of the product

3. **Intended use or uses** of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**EN 15651-1:2012 Type F-EXT-INT-CC**

non-structural facade sealant intended for sealing exterior wall joints, window and door perimeter joints in building construction, including the interior face (intended for use in cold climates)

**EN 15651-2:2012 Type G-CC**

non-structural elastic sealant used for sealing glazing in building construction applications (intended for use in cold climates)

**EN 15651-3:2012 Type S Class S 1**

sealant used for sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurised water

4. Name, registered trade name or registered trade mark and contact address of the **manufacturer** as required pursuant to Article 11(5):

Don Construction Products Bulgaria EAD, 152, Prof.Tsvetan Lazarov Blvd., Sofia 1582, Bulgaria

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

6. **System or systems of assessment** and verification of constancy of performance of the construction product as set out in Annex V:

system 3 for type of testing  
system 3 for the reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a **harmonised standard**:

The notified body Tecnalía, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: a test report

The notified body Tecnalía, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: classification report

8. In case of the declaration of performance concerning a construction product for which a **European Technical Assessment** has been issued:

not relevant

9. Declared performance

**EN 15651-1:2012 Type F-EXT-INT-CC**

Conditioning: Method A  
Substrate: glass without primer

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501-1:2007+A1	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	EN 15651-1:2012; 4.5	EN 15651-1:2012
Water tightness and air tightness:			
Resistance to flow	≤ 3 mm	modified EN ISO 7390	EN 15651-1:2012
Loss of volume	≤ 45 %	EN ISO 10563	EN 15651-1:2012
Tensile properties (i.e. elongation): - after immersion in water at (23 °C)	NPD	EN ISO 10591	EN 15651-1:2012
Tensile properties (i.e. elongation): -at maintained extension after water immersion	NF	EN ISO 10590	EN 15651-1:2012
Tensile properties (i.e. secant modulus): -for non-structural low modulus sealants used in joints in cold climate areas (-30°C)	≤ 0,9 Mpa	modified EN ISO 8339	EN 15651-1:2012
Tensile properties (i.e. at maintained extension): -for non-structural sealants used in joints in cold climate areas (-30°C)	NF	modified EN ISO 8340	EN 15651-1:2012
Durability	Pass	EN ISO 8339, EN ISO 8340, EN ISO 9047, EN ISO 10590	EN 15651-1:2012

**EN 15651-2:2012 Type G-CC**

Conditioning: Method A

Substrate: glass without primer

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501-1:2007+A1	EN 15651-2:2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	EN 15651-1:2012; 4.5	EN 15651-2:2012
Water tightness and air tightness:			
Loss of volume	≤ 40 %	EN ISO 10563	EN 15651-2:2012
Vertical flow resistance	≤ 3 mm	modified EN ISO 7390	EN 15651-2:2012
Adhesion/cohesion properties after exposure to heat water and artificial light	NF	EN ISO 11431	EN 15651-2:2012
Elastic recovery	≥ 60 % at 60% elongation	EN ISO 7389	EN 15651-2:2012

Tensile properties (i.e. secant modulus): -for non-structural low modulus sealants used in joints in cold climate areas (-30°C)	≤ 0,9 Mpa	modified EN ISO 8339	EN 15651-2:2012
Tensile properties (i.e. at maintained extension): -for non-structural sealants used in joints in cold climate areas (-30°C)	NF	modified EN ISO 8340	EN 15651-2:2012
Durability	Pass	EN ISO 8339, EN ISO 8340, EN ISO 9047, EN ISO 10590	EN 15651-2:2012

**EN 15651-3:2012 Type S**

Conditioning: Method A

Substrate: glass without primer

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501-1:2007+A1	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	EN 15651-1:2012; 4.5	EN 15651-3:2012
Water tightness and air tightness:			
Resistance to flow	≤ 3 mm	modified EN ISO 7390	EN 15651-3:2012
Loss of volume	≤ 55 %	EN ISO 10563	EN 15651-3:2012
Tensile properties (i.e. elongation): - after immersion in water at (23 °C)	≥ 25 %	EN ISO 10591	EN 15651-3:2012
Tensile properties (i.e. elongation): - at maintained extension after water immersion	NPD	EN ISO 10590	EN 15651-3:2012
Microbiological growth	0	EN ISO 846:1997, procedure B	EN 15651-3:2012
Durability	Pass	EN ISO 8340, EN ISO 846, EN ISO 9046, EN ISO 10591	EN 15651-3:2012



# DECLARATION OF PERFORMANCE



Page: 4

according Annex III of the Regulation (EU) No 305/2011 DCDoP-070003-021B  
Edition: 06.07.2021

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the  
manufacturer by:

Branimir Nikolov  
(Marketing & Specification Manager)



06.07.2021, Sofia

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU)No. 1907/2006 (REACH), Annex II is annexed to this Declaration of Performance