

DonFill Joint

Ready to use interior grade jointing compound for gypsum boards



DESCRIPTION

DonFill Joint is a ready to use, high performance jointing compound for gypsum boards. DonFill Joint provides a flexible, easy to apply jointing compound with excellent crack resistance and adhesion to gypsum and other common building surfaces.

APPLICATIONS

- › DonFill Joint is designed for use internally, to fill joints between adjacent gypsum boards in conjunction with an appropriate mesh or paper tape.
- › Used for covering corner bead, fasteners and other small openings.
- › Can be used for finishing and skimming the entire gypsum board surface. However, to achieve an ultra smooth finish, Doncoat is recommended.

ADVANTAGES

- › Pre-mixed, ready to apply.
- › Quick drying.
- › Excellent adhesion.
- › Adhesion unaffected under humid conditions.
- › Does not flake off.
- › Environmentally friendly.

METHOD OF USE

PREPARATION

Stir contents lightly without adding water, avoid over mixing as it may cause air entrapment. Do not mix with any other material. Joints and all surfaces should be dry, clean, and free from dust or dirt.

APPLICATION

For filling the joints between gypsum or cement boards, cover the joint with DonFill Joint using a proper stainless steel putty knife and then embed paper tape or glass fiber mesh while DonFill Joint is still wet.

Allow drying then apply another layer of DonFill Joint over the joint and leave it to dry prior to sanding with fine sandpaper. If needed further coats can be applied to fill the joints completely, consider the drying time between each coat.

TECHNICAL PROPERTIES:

Appearance:	Smooth, creamy, lump free paste
Colour:	White
Density:	1.75 ± 0.10 g/cm ³
Skimming time:	10 - 20 min
VOC:	< 10 g/ ltr
ASTM D2369	(comply with LEED)

Note: If required, DonFill Joint can be slightly diluted with clean water for ease of application. Contact DCP's technical department for further details.

CLEANING

Wash tools with warm, soapy water. Wipe tools dry to prevent rusting.

CONSUMPTION

Approximately 1.75 kg/m² @ 1 mm thickness.

PACKAGING

DonFill Joint is available in 28 kg buckets.

STORAGE

Keep tightly sealed, store under cover in a dry area at room temperature, protect from freezing, exposure to extreme heat and direct sunlight.

SHELF LIFE

DonFill Joint has a shelf life of 12 months from date of manufacture if stored in original unopened buckets.

If these conditions are exceeded, DCP Technical Department should be contacted for advice.

DCP Saudi Co.

Sulay, Industrial Area, Istanbul St., Riyadh
Industrial City 3, Jeddah
Saudi Arabia
info.saudi@dcp-int.com
www.dcp-int.com





DonFill Joint

CAUTIONS

HEALTH AND SAFETY

Wear suitable protective clothing, gloves and eye/face protection.
Should accidental skin contact occur, remove immediately with clean water.

For further information refer to the Material Safety Data Sheet.

FIRE

DonFill Joint is nonflammable.

MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

DCP Saudi Co.

Sulay, Industrial Area, Istanbul St., Riyadh
Industrial City 3, Jeddah
Saudi Arabia
info.saudi@dcp-int.com
www.dcp-int.com

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

www.dcp-int.com

DCP Building Excellence



11-0066-KSA-A-2024